


Modelo / Model / Modelo

BPC - 17,5 JO2-110



Umáx. / Um / Umax.	(kV)	17,5
Tensão Sup. / Rated Pow. Freq. / Ens. Dielec.	(kV)	50
NBI / BIL / BIL	(kV)	110
It. / Ith. / I ter.	(x In - 1s)	25
Id. / Idyn. / Idin.	(x In cr)	62,5
Dist. Escoam. / Creep. Distan. / Dist. Fuga.	(mm)	660
Massa / Mass / Masa	(kg)	Tabela abaixo / Table below / Tabela abajo
Temp. Trab. / Work Temp. / Temp. Trab.	(°C)	-20 até / up to / hasta +75°C
Cor / Color / Cor		Cinza/Grey/Gris RAL 7030
Flexão / Bending / Flexion	(N)	2000

Modelo Model Modelo	Versão / Version / Versión 1 (Sem TC / Without CT / Sin TC)							Versão / Version / Versión 2						Versão / Version / Versión 3					
	L	L1	L2	L3	D	Massa Mass Masa	L	L1	L2	L3	D	Massa Mass Masa	L	L1	L2	L3	D	Massa Mass Masa	
400	545	55	180	0	M16x2	7,8	755	55	390	220	M16x2	11,1	685	55	320	150	M16x2	10,0	
600	545	55	180	0	M20x2	8,7	755	55	390	220	M20x2	12,2	685	55	320	150	M20x2	11,0	
800	545	55	180	0	M20x2	9,0	755	55	390	220	M20x2	12,9	685	55	320	150	M20x2	11,6	
1250	595	80	180	0	M36x2	12,1	805	80	390	220	M36x2	15,7	735	80	320	150	M36x2	15,2	
1600	595	80	180	0	M36x2	13,1	805	80	390	220	M36x2	17,9	735	80	320	150	M36x2	16,2	
2000	615	90	180	0	M36x2	15,3	825	90	390	220	M36x2	21,3	755	90	320	150	M36x2	19,3	
2500	615	90	180	0	M36x2	16,8	825	90	390	220	M36x2	23,3	755	90	320	150	M36x2	21,1	

Dimensões / Dimensions / Dimensiones (mm)

